

KEOR Multiplug

Multi outlets UPS
from 600 and 800 VA



UPS for (digital) homes, shops, hotels.

This is the perfect solution to ensure a safe and high quality energy supply to modem, router, Smart TV, home entertainment systems, POS, cash machine. It's equipped by a USB charger to recharge smartphone or tablet.



Keor Multiplug

Single phase VI



3 100 83

Automatic start-up: when there is no mains supply or it is of poor quality, the UPS continues working using a battery and switches off if the network breaking time exceeds the back-up time.

Technical characteristics

- Replaceable fuse for fine protection in case of short-circuits
- LED indicators
- Internal AVR (Automatic Voltage Regulator)
- USB Charger
- Available outputs sockets in German or French type

Pack	Cat. No.		Multi-socket UPS			
	French standard	German standard	Nominal power (VA)	Active power (W)	Back-up time ⁽¹⁾ (min)	No. of sockets
1	3 100 83	3 100 81	600	360	up to 15	4+2
1	3 100 84	3 100 82	800	480	up to 15	4+2

NOTE: The stated back-up times in minutes are estimated and may vary according to the load characteristics, operating conditions and environment.

Keor Multiplug

Single phase VI

Characteristics

General characteristics	3 100 83 3 100 81	3 100 84 3 100 82
Nominal power (VA)	600	800
Active power (W)	360	480
Technology	Line Interactive VI	
Waveform	Simulated SineWave	

Input characteristics

Input voltage	230 V
Input frequency	50-60 Hz +/- 5Hz
Input voltage range	170 V-290 V

Output characteristics

Output voltage	230 V ± 10%
Output frequency (nominal)	50/60 Hz +/- 1 Hz
USB charger/Voltage	Type A female/5 V

Mechanical characteristics

Dimensions W x H x D (mm)	190 x 89.5 x 296	
Net weight (kg)	5	5,5

Ambient conditions

Ambient operating temperature (°C)	0 to 40°C
Relative humidity (%)	< 95% non-condensing
Noise at 1 m (dBA)	< 40

Certifications

Reference product standards	EN 62040-1, EN 62040-2
-----------------------------	------------------------