Absorbed loads
max 20A:
- electric engines
- induction hobs
- electric ovens
- other

Absorbed loads
max 16A

Switchboard

Max. 500W

> 5 W
< 300 W

Max 16A

max 500VA

① Connected
two-way
switch

Traditional
two-way
switch

Traditional
push-button

Traditional
push-button

③ Connected relay

④ Connected socket

⑤ Connected
Shutter
control

Measurement
toroid

L

N

Connected DIN
energy meter
art. F20T60A

Connected
contactor
art. FC80CC

Connected
relay
art. FC80RC

② Gateway

App HOME + CONTROL

Modem Wi-Fi

SET
MIN

Thermostat Smarther
item. XW8002, item. XG8002, item XM8002
and item. XW8002W

Optional controls for system expansion via radio - wall installation

⑥ Wireless Home&Away
scenario control

⑦ Wireless Wakeup&Sleep
scenario control

⑧ Wireless light control

⑨ Wireless shutter control

Device legend

Ref.	Ref. Living Now with Netatmo	Ref. Livinglight with Netatmo
1	K4003C	L/N/NT4003C
2	K4500C	L/N/NT4500C
3	3584C	3584C
4	K4531C	L/N/NT4531C
5	K4027C	L/N/NT4027C
6	K4570CW	L/N/NT4570CW
7	K4574CW	L/N/NT4574CW
8	K4003CW	L/N/NT4003CW
9	K4027CW	L/N/NT4027CW